

## UV GLASS PRIMER

Revision date: 28.03.2025

Page 1 of 12

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

UV GLASS PRIMER

**Further trade names**

UV- Glasprimer

UV primaire réparation

Imprimación UV para impactos

UFI: Q281-S7PX-Y65N-8WJU

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Primer / adhesion promoter

**Uses advised against**

No information available.

**1.3. Details of the supplier of the safety data sheet**

Company name: PMA/TOOLS GmbH  
Street: Siemensring 42  
Place: D-47877 Willich - Germany  
Telephone: +49 2154 922230  
E-mail: info@pma-tools.de  
Contact person: Labor  
E-mail: msds@pma-tools.de (Please DO NOT use for requesting Safety Data Sheets.)  
Internet: www.pma-tools.de  
Responsible Department: Laboratory

**1.4. Emergency telephone number:**

Telephone number of the company in case of emergencies (24 h):  
+49 (0) 700 / 24 112 112 (PMR)  
+1 872 5888271 (PMR)

Emergency information services / official advisory body:  
<UK> National Poisons Information Service (24 h): 0870 600 6266 (UK only)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

Flam. Liq. 2; H225

Eye Irrit. 2; H319

STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

**2.2. Label elements****GB CLP Regulation****Hazard components for labelling**

acetone; propan-2-one; propanone

**Signal word:** Danger**Pictograms:**

## UV GLASS PRIMER

Revision date: 28.03.2025

Page 2 of 12

**Hazard statements**

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

**Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves/protective clothing and eye protection/face protection.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P370+P378	In case of fire: Use extinguishing powder to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

**Special labelling of certain mixtures**

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

**2.3. Other hazards**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

## SECTION 3: Composition/information on ingredients

**3.2. Mixtures****Chemical characterization**

Mixture of the following substances with non-hazardous additions.

**Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
67-64-1	acetone; propan-2-one; propanone			95 - < 100 %
	200-662-2	606-001-00-8	01-2119471330-49	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
67-64-1	200-662-2	acetone; propan-2-one; propanone	95 - < 100 %
	inhalation: LC50 = 76 mg/l (vapours); dermal: LD50 = 20000 mg/kg; oral: LD50 = 5800 mg/kg		

## SECTION 4: First aid measures

**4.1. Description of first aid measures****General information**

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down. Never give anything by mouth to an unconscious person or a person with cramps. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

**UV GLASS PRIMER**

Revision date: 28.03.2025

Page 3 of 12

**After inhalation**

Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. Medical treatment necessary.

If unconscious but breathing normally, place in recovery position and seek medical advice.

**After contact with skin**

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

**After contact with eyes**

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

**After ingestion**

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Call a physician in any case!

**4.2. Most important symptoms and effects, both acute and delayed**

May cause drowsiness or dizziness. Causes serious eye irritation.

Gastrointestinal complaints, Headache.

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Foam. Dry extinguishing powder. Carbon dioxide (CO<sub>2</sub>). Water spray jet.

Co-ordinate fire-fighting measures to the fire surroundings.

**Unsuitable extinguishing media**

Full water jet

**5.2. Special hazards arising from the substance or mixture**

Highly flammable. Vapours can form explosive mixtures with air.

In case of fire may be liberated: Carbon monoxide.(CO), Carbon dioxide (CO<sub>2</sub>), Gases/vapours, toxic

**5.3. Advice for firefighters**

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration. Use personal protection equipment. Avoid contact with skin, eyes and clothes.

**6.2. Environmental precautions**

Do not allow uncontrolled discharge of product into the environment. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

**6.3. Methods and material for containment and cleaning up****Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Unsuitable material for taking up: Sawdust (Combustible substance)!

Treat the recovered material as prescribed in the section on waste disposal.

## UV GLASS PRIMER

Revision date: 28.03.2025

Page 4 of 12

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Provide adequate ventilation. If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. When using do not eat, drink, smoke, sniff.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

#### Advice on general occupational hygiene

Always close containers tightly after the removal of product. When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work. Take off contaminated clothing and wash it before reuse. Used working clothes should not be worn outside the work area. Street clothing should be stored separately from work clothing.

Keep away from food, drink and animal feedingstuffs.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

#### Hints on joint storage

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances. Reducing agent, Strong acid strong base.

Keep away from food, drink and animal feedingstuffs.

#### Further information on storage conditions

Protect from direct sunlight.

storage temperature: 5 - 30 °C

### 7.3. Specific end use(s)

No information available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL

## UV GLASS PRIMER

Revision date: 28.03.2025

Page 5 of 12

### DNEL/DMEL values

CAS No	Substance		
DNEL type	Exposure route	Effect	Value
67-64-1	acetone; propan-2-one; propanone		
Worker DNEL, acute	inhalation	systemic	2420 mg/m <sup>3</sup>
Worker DNEL, acute	inhalation	local	2420
Worker DNEL, long-term	dermal	systemic	186 mg/kg bw/day
Worker DNEL, long-term	inhalation	systemic	1210 mg/m <sup>3</sup>

### PNEC values

CAS No	Substance	
Environmental compartment	Value	
67-64-1	acetone; propan-2-one; propanone	
Freshwater	10,6 mg/l	
Marine water	1,06 mg/l	
Freshwater sediment	30,4 mg/kg	
Marine sediment	3,04 mg/kg	
Micro-organisms in sewage treatment plants (STP)	100 mg/l	
Soil	29,5 mg/kg	

### 8.2. Exposure controls



#### Appropriate engineering controls

Use only outdoors or in a well-ventilated area.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Do not breathe dust/fume/gas/mist/vapours/spray.

In case of dangerous gases, vapours or dusts self-contained breathing apparatus or suitable masks and filters need to be advised.

In case of inadequate ventilation wear respiratory protection.

#### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Suitable eye protection: goggles. (EN 166).

Avoid contact with eyes and skin.

##### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Wear suitable gloves. (EN 374).

Recommended material: Butyl caoutchouc (butyl rubber)

Thickness of the glove material:  $\geq 0,7$  mm

Breakthrough time:: Index No. 2, > 30 Min. / Index No. 6, > 480 Min.

Replace when worn.

Recommendation: Use protective skin cream before handling the product.

## UV GLASS PRIMER

Revision date: 28.03.2025

Page 6 of 12

**Skin protection**

Use personal protection equipment.

Wear anti-static footwear and clothing

When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn. (89/686/EWG).

Recommended protective clothing articles: compliant EN 14605 / EN 13982

**Respiratory protection**

In case of dangerous gases, vapours or dusts self-contained breathing apparatus or suitable masks and filters need to be advised. In case of inadequate ventilation wear respiratory protection.

Suitable respiratory protection apparatus: (EN 140, EN 136) particle filter ABEK-P2, (EN 14387)

### SECTION 9: Physical and chemical properties

**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	colourless
Odour:	characteristic
Odour threshold:	No data available

**Changes in the physical state**

Melting point/freezing point:	-94 °C
Boiling point or initial boiling point and boiling range:	57 °C
Flash point:	- 7 °C

**Flammability**

Solid/liquid:	not applicable
	not applicable

**Explosive properties**

No data available

Lower explosion limits:	2 vol. %
Upper explosion limits:	13 vol. %
Auto-ignition temperature:	265 °C

**Self-ignition temperature**

Solid:	not applicable
Gas:	not applicable

Decomposition temperature: No data available

pH-Value (at 20 °C): 7

Viscosity / dynamic: (at 20 °C) 0,33 mPa·s

Viscosity / kinematic: No data available

Water solubility: No data available

**Solubility in other solvents**

No data available

Partition coefficient n-octanol/water: No data available

Vapour pressure: (at 20 °C) 241,16 hPa

Vapour pressure: (at 50 °C) 802,1733 hPa

Density (at 20 °C): 0,793 g/cm<sup>3</sup>

Relative vapour density: No data available

## UV GLASS PRIMER

Revision date: 28.03.2025

Page 7 of 12

Particle characteristics: not applicable

**9.2. Other information****Information with regard to physical hazard classes**

Oxidizing properties

No data available

**Other safety characteristics**

Solid content:

not applicable

Evaporation rate:

No data available

**Further Information**

No data available

## SECTION 10: Stability and reactivity

**10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

**10.2. Chemical stability**

The product is chemically stable under recommended conditions of storage, use and temperature.

**10.3. Possibility of hazardous reactions**

No hazardous reaction when handled and stored according to provisions.

Highly flammable liquid and vapour. In use may form flammable/explosive vapour-air mixture.

**10.4. Conditions to avoid**

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Protect from direct sunlight.

**10.5. Incompatible materials**

Oxidising agent. Pyrophoric or self-heating substances. Reducing agent, Strong acid strong base.

Phosphoroxchlorid, Chloroform, peroxides, for example hydrogen peroxide.

**10.6. Hazardous decomposition products**

Decomposition products in case of fire: see section 5.

## SECTION 11: Toxicological information

**11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix calculated**

ATE (oral) &gt; 2000 mg/kg; ATE (dermal) &gt; 2000 mg/kg; ATE (inhalation vapour) &gt; 20 mg/l; ATE (inhalation dust/mist) &gt; 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-64-1	acetone; propan-2-one; propanone				
	oral	LD50 mg/kg	5800	Rat	RTECS
	dermal	LD50 mg/kg	20000	Rabbit	IUCLID
	inhalation (4 h) vapour	LC50	76 mg/l	Rat	

**Irritation and corrosivity**

## UV GLASS PRIMER

Revision date: 28.03.2025

Page 8 of 12

Serious eye damage/eye irritation: Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

### Sensitising effects

Based on available data, the classification criteria are not met.

### Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

### STOT-single exposure

May cause drowsiness or dizziness. (acetone; propan-2-one; propanone)

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

### Aspiration hazard

Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### Endocrine disrupting properties

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

### Other information

No information available.

## SECTION 12: Ecological information

### 12.1. Toxicity

There are no data available on the mixture itself. The ecotoxicological properties of this mixture are determined by the ecotoxicological properties of the single components (see section 3).

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
67-64-1	acetone; propan-2-one; propanone					
	Acute fish toxicity	LC50 mg/l	5540	96 h	Oncorhynchus mykiss	
	Acute crustacea toxicity	EC50 mg/l	6100	48 h	Daphnia magna	
	Crustacea toxicity	NOEC mg/l	2212		Daphnia magna	

### 12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
67-64-1	acetone; propan-2-one; propanone				
	OECD 301B	91 %	28		
	Readily biodegradable (according to OECD criteria).				

### 12.3. Bioaccumulative potential

The product has not been tested.

## UV GLASS PRIMER

Revision date: 28.03.2025

Page 9 of 12

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
67-64-1	acetone; propan-2-one; propanone	-0,24

**12.4. Mobility in soil**

The product has not been tested.  
(Acetone) Henry's Law Constant: 2,929 Pa m<sup>3</sup>/mol / 25 °C (ECHA)

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

No information available.

**Further information**

Avoid release to the environment. Do not allow to enter into surface water or drains.

### SECTION 13: Disposal considerations

**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation. The waste key according to the European Waste Catalogue (EWC number) refers to the real wastes origin and therefore is not product- but use-oriented. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Recommendation: EAK 200129

**List of Wastes Code - residues/unused products**

200129 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS; separately collected fractions (except 15 01); detergents containing hazardous substances; hazardous waste

**Contaminated packaging**

Dispose of waste according to applicable legislation. Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

### SECTION 14: Transport information

**Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	UN 1090
<b>14.2. UN proper shipping name:</b>	ACETONE
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3



Classification code:	F1
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

**Inland waterways transport (ADN)**

<b>14.1. UN number or ID number:</b>	UN 1090
--------------------------------------	---------

### UV GLASS PRIMER

Revision date: 28.03.2025

Page 10 of 12

**14.2. UN proper shipping name:** ACETONE  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



Classification code: F1  
 Limited quantity: 1 L  
 Excepted quantity: E2

**Marine transport (IMDG)**

**14.1. UN number or ID number:** UN 1090  
**14.2. UN proper shipping name:** ACETONE  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



Special Provisions: -  
 Limited quantity: 1 L  
 Excepted quantity: E2  
 EmS: F-E, S-D

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** UN 1090  
**14.2. UN proper shipping name:** ACETONE  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



Limited quantity Passenger: 1 L  
 Passenger LQ: Y341  
 Excepted quantity: E2  
 IATA-packing instructions - Passenger: 353  
 IATA-max. quantity - Passenger: 5 L  
 IATA-packing instructions - Cargo: 364  
 IATA-max. quantity - Cargo: 60 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

Warning: Combustible liquid.

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

## SECTION 15: Regulatory information

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

**UV GLASS PRIMER**

Revision date: 28.03.2025

Page 11 of 12

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2004/42/EC on VOC in  
paints and varnishes: 99,1 %Information according to Directive  
2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Changes**This data sheet contains changes from the previous version in section(s):  
1,2,3,4,5,6,7,8,9,10,11,12,13,14,15,16.**Abbreviations and acronyms**

ADN: Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways).

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road).

ATE: Acute Toxicity Estimate.

AwSV: Anlagenverordnung wassergefährdender Stoffe (Regulation on facilities handling substances dangerous to water).

BGI: Berufsgenossenschaftliche Informationen (trade association information).

BGR: Berufsgenossenschaftliche Regeln (trade association regulation).

CAS: Chemical Abstracts Service.

CEN: Comité Européen de Normalisation European (Committee for Standardization).

CLP: Classification, Labelling and Packaging of substances and mixtures (REGULATION (EC) No 1272/2008).

DIN: Deutsches Institut für Normung (German institute for standardization).

DMEL: Derived Minimum Effect Level.

DNEL: Derived No Effect Level.

EC: European Community.

EC50: Half maximal effective concentration.

ECHA: European Chemicals Agency.

EG: Europäische Gemeinschaft (European Community).

EINECS: European Inventory of Existing Commercial Chemical Substances.

ELINCS: European List of Notified Chemical Substances.

EN: European Norms.

GHS: Globally Harmonized System of Classification and Labelling of Chemicals.

IATA-DGR: International Air Transport Association - Dangerous Goods Regulations.

IBC: Intermediate Bulk Container.

IC50 / ErC50: Inhibitory concentration, 50 %.

ICAO-TI: International Civil Aviation Organization - Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IMDG: International Maritime Code for Dangerous Goods.

ISO: International Organization for Standardization.

IUPAC: International Union for Pure and Applied Chemistry.

LC50: Lethal concentration, 50 %.

## UV GLASS PRIMER

Revision date: 28.03.2025

Page 12 of 12

LD50: Lethal dose, 50 %.

log Kow (Pow): Partition coefficient n-octanol/water.

LQ: Limited Quantities.

MARPOL: International Convention for the Prevention of Marine Pollution from Ships.

OECD: Organisation for Economic Co-operation and Development.

PBT: persistent, bioaccumulative and toxic.

PNEC: Predicted No Effect Concentration.

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006).

RID: Règlement concernant le transport International ferroviaire de marchandises Dangereuses (Regulation concerning the International Carriage of Dangerous Goods by Rail).

SVHC: Substances of Very High Concern.

STOT - RE: Specific Target Organ Toxicity - Repeated Exposure.

STOT - SE: Specific Target Organ Toxicity - Single Exposure.

TRGS: Technische Regel für Gefahrstoffe (technical guideline for the handling of hazardous materials).

UFI: Unique Formula Identifier.

UN: Untied Nations.

VOC: Volatile organic compounds.

vPvB: very persistent and very bioaccumulative.

WGK: Wassergefährdungsklasse (water hazard class).

**Classification for mixtures and used evaluation method according to GB CLP Regulation**

Classification	Classification procedure
Flam. Liq. 2; H225	
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method

**Relevant H and EUH statements (number and full text)**

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

**Further Information**

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*